

**Classification**

- A. Receptions
- B. Desk-mounted receptions

**A. Receptions**

**A.1. Technical Data of Receptions**

- A.1.1. The desk tops are made of double-side melamine film covered 3-layer chipboard E1. The desk tops and side legs are 25 mm thick, the modesty panels and side panels are 18 mm thick.
- A.1.2. The bottom part of the reception-desk is formed by two side legs which are connected together through a frame with metal components. Side panels are mounted on the frame internally and externally, thus forming a “Π” shaped base, over which the desktop is mounted.
- A.1.3. The desk top has two powder coated metal cable grommets for the routing of cables.
- A.1.4. In the case of reception compositions the intermediate side legs have a curved side for easy and ergonomical movement of the user along the whole length of the reception.

**B. Desktop mounted receptions**

**B.1. Technical Data of Desk-mounted Receptions**

- B.1.1. The desk tops are made of double-side melamine film covered 3-layer chipboard E1. The desk tops and side legs are 25 mm thick, the modesty panels are 18 mm thick.
- B.1.2. The top part of the desk-mounted receptions is formed by two side legs which are connected together through panels, thus forming a “Π” shaped base, over which the reception top is mounted. The reception top can be either of wood or of glass.
- B.1.3. The glass of the desk-mounted reception is 10mm thick securite, chemically sandblasted.

Packaging of 1 piece of straight reception (1600x800x750H mm)

Weight: 76,0 kg

Volume: 0,32 m<sup>3</sup>

Packets: 4

Packaging of 1 piece of desktop mounted (1600x350x360H mm)

Weight: 18,0 kg

Volume: 0,07 m<sup>3</sup>

Packets: 2

### **PRODUCT CERTIFICATES:**

EN 14073-2:04

EN 527-1:00

EN 527-2:04

EN 527-3:03

